



2026

# CONTROL CONTRACTOR

Scalable, Integrated, Installed Audio Solutions

VERSION 3.11.2026



# Contents Guide

|   |            |
|---|------------|
| <b>About JBL</b> .....                              | <b>3-5</b> |
| <b>Ceiling Loudspeakers</b> .....                   | 6-18       |
| <b>Control 400 Ceiling Speaker Family</b> .....     | 6-13       |
| <b>Control 200 Series Medium-Format</b> .....       | 14         |
| <b>Control 300 Series Large-Format</b> .....        | 15         |
| <b>CSS Commercial Series</b> .....                  | 16         |
| <b>8100 Series with Stylized Grille</b> .....       | 17         |
| <b>Lay-In Ceiling-Tile Speakers</b> .....           | 18         |
| <b>Pendant Loudspeakers</b> .....                   | 22-23      |
| <b>Control 60 Series</b> .....                      | 22-23      |
| <b>In-wall Loudspeakers</b> .....                   | 24-25      |
| <b>Control Contractor 100 Series</b> .....          | 24-25      |
| <b>Surface-mount Speakers</b> .....                 | 26-39      |
| <b>SLP Series Sleek Low-Profile</b> .....           | 26-27      |
| <b>Control Contractor 20 Series</b> .....           | 30-32      |
| <b>Control 50 Series Subwoofer/Satellite</b> .....  | 33         |
| <b>Control CRV Architectural</b> .....              | 36         |
| <b>Control HST Wide-Coverage</b> .....              | 37         |
| <b>CSS Commercial Series</b> .....                  | 38         |
| <b>Control Pro Series</b> .....                     | 39         |
| <b>Column Speakers</b> .....                        | 40-43      |
| <b>COL Series</b> .....                             | 40         |
| <b>CBT Series</b> .....                             | 42-43      |
| <b>Landscape Loudspeakers</b> .....                 | 44-49      |
| <b>GSF Series Garden Ground-Stake</b> .....         | 44-45      |
| <b>GSB Series Garden In-Ground Subwoofers</b> ..... | 46-47      |
| <b>Control 80 Series</b> .....                      | 48-49      |
| <b>Understanding Control Contractor</b> .....       | <b>50</b>  |
| <b>Suffix and Prefix Guide</b> .....                | <b>51</b>  |



# About JBL

## Power and versatility are only the beginning.

When it comes to the listening experience, JBL never ceases to push the boundaries. From its inception over 75 years ago, the brand has grown to become synonymous with epic sound. And while the enjoyment is instinctive, the science behind each and every innovation is precise and methodical. Passionate and gifted engineers and designers around the world devote themselves to developing JBL products and solutions that take listening to the next level - and they've been doing it since day one.

Today, JBL professional solutions encompass recording studios, movie theaters, tour sound, installed sound, arenas and stadiums, and much more. At the heart of each of these solutions is a meticulous attention to detail, a willingness to develop everything from the ground up, and an absolute dedication to giving artists outstanding sound, whether they're performing at a major music festival or busking on a street corner. And the technologies that JBL develops for its professional audience benefit all of JBL's listeners as they are distilled into smaller form factors, allowing people everywhere to enjoy professional-quality sound at a convenient size and an affordable price.

Over the decades, JBL has contributed a remarkable number of industry firsts and technical innovations that further cemented its reputation as an audio pioneer,

garnering Grammy® awards, Academy awards, and widespread recognition from the world's most celebrated musicians and consumers along the way.

Expertly blending a bold vision of the future with the passion and talent of its engineers and designers, JBL develops its own solutions, invents its own technologies, and creates its own tools with a pioneering spirit that has defined the brand for the past 75 years. Today, JBL is present in more than 130 countries, encompasses an increasingly diverse range of next-level products and solutions, and has over 300 patents to its name, such as VGC™ transducer technology, Slip Stream™ low frequency port, Progressive Transition™ (PT) waveguides, and Plus One™ woofer cone technology.

Thanks to a truly exceptional dedication to consistently deliver exactly what customers desire, JBL sound has become part of the fabric of people's lives. Whether it's cinema sound that makes the movie-going experience more immersive, soundbars that transform the living room into a concert hall, portables that let listeners enjoy their favorite tunes wherever they go, gaming headsets that make players swear they've just stepped into the game, or in-car audio technology that turns the daily commute into a moment of pure listening pleasure, JBL fills listeners' lives with sound as it was meant to be heard.



# A Journey of Engineering Excellence

Audio technology is at the core of everything JBL does. For over 75 years, they have employed the best methodology and tools, developing everything from the ground up, guaranteeing their efforts exceed the needs and expectations of audio professionals throughout the world. Never straying from this exacting formula, this journey has produced a prolific list of audio achievements, ground-breaking technologies, revolutionary advances in the art and science of professional audio, many patents, and many awards. It's a journey that is legendary worldwide and has positioned JBL as the world leader in professional audio. Not just as a brand, but as a company known for consistently blending creativity and science as a manifestation of their passion for sound and commitment to those who create it.

## Transducers.

The technology of transducers is truly the starting place for the entire JBL engineering legacy. Building on founder James B. Lansing's historic foundation, JBL engineers continue to break ground on new and better ways to design transducers, reaching beyond what is commonly understood as possible and consistently setting new performance benchmarks for the audio industry. Starting from scratch and often developing patents in the process, has resulted in technologies such as Differential Drive woofers, CMCD Cone Midrange drivers, and

the D2 Dual Voice Coil Compression Driver, that cover the entire practical bandwidth of professional audio devices. Simultaneously addressing performance-robbing challenges such as power compression, heat dissipation, distortion, component weight, and physical footprint, JBL has created a range of transducers that are unparalleled in their ability to deliver extraordinary performance throughout a wide range of applications.

### Differential Drive®

JBL's exclusive dual voice coil, dual magnetic gap Differential Drive technology reduces weight while enhancing all critical performance parameters including better heat dissipation, lower power compression and higher dynamic range versus conventional single-coil designs. This allows very high output with minimal power compression, resulting in deep distortion-free bass even at very high SPL. Differential Drive® technology is now at the core of a full range of woofer models incorporated in many JBL loudspeaker systems from touring sound and fixed installation to studio and cinema sound.

### D2 Dual Diaphragm Dual Voice Coil Compression Driver

The revolutionary D2 Dual Driver dramatically improves the sound and performance of high frequencies, providing an extreme output advantage over conventional systems with significantly higher array power, reduced distortion, double the number of voice coils and more

than double the powerhandling. This results in a dramatic increase in pure high-frequency sound pressure levels in the same physical footprint with a 30% reduction in weight.

## Directivity.

Building better loudspeakers is only the first of many performance challenges that face all audio design engineers. Controlling the sound as it leaves the speaker enclosure is as critical to the performance of the system as the quality of the source component. The goal is always the same: create a consistent sound pattern throughout the desired vertical and horizontal plane without introducing artifacts, while ensuring the full bandwidth and SPL capability of the transducers, and providing a seamless transition from high frequency to low frequency components. JBL engineers relentlessly test new shapes and develop new materials to achieve the desired performance, often inventing new testing methodologies to ensure that nothing is left out of a thorough and rigorous examination of the design. The resulting technology has produced such ground-breaking designs as the Progressive Transition Waveguide, Image Control Waveguide, Slip Stream Port, Radiation Boundary Integrator, and Constant Curvature Waveguide. With multiple patents, and many successful installations in use worldwide, this critical component of JBL technology continues to evolve through our continuous pursuit of better, more accurate sound.

### Radiation Boundary Integrator™ (RBI) and Coplanar RBI (CRBI™)

JBL's patented Radiation Boundary Integrator combines the high frequency and mid-range so the transition across each band is uninterrupted, undistorted and seamless. A patented, tuned resonant chamber is integrated



into the waveguide itself, effectively eliminating throat-related cancellations due to back pressure from the mid-range section. Our refined RBI waveguide implementation provides improved horizontal coverage - broader and more stable.

CRBI™ Technology is designed to deliver especially smooth sound character that remains consistent, clear, and pleasant across a wide coverage area. It reduces on-axis hot spots and off-axis cold spots and improves the listening experience for users as they move throughout a space. This enhanced coverage can result in fewer speakers, amplifier channels, and project costs, required to cover a space.

## Testing.

All audio products have a useful life, and JBL engineers are committed to making that as long as possible, not only in terms of reliability, but also in terms of how good the sound is, the very first time a system is turned on. Every JBL Professional product undergoes stringent testing above and beyond what the product would face when deployed in the real world.

JBL has multiple application-specific anechoic testing chambers and has developed the only known 'Speaker Shuffler' that allows rapid and precise re-positioning of speaker systems in the exact same space for truly accurate A/B testing. This rigorous, uncompromising adherence to testing results in continuous breakthroughs in performance and ensures that JBL users worldwide can always work with confidence.





# CONTROL 400

CEILING SPEAKER FAMILY

## The Next Generation of Performance and Reliability



**STANDARD  
COVERAGE  
SERIES**



**ENHANCED  
COVERAGE  
SERIES**



**PREMIUM  
COVERAGE  
SERIES**



**Full-Face magnetic grilles for modern decors**




**Optimized for efficient and reliable installation**



**Multiple low-profile models**

# Control 400 Series



## Standard Coverage Ceiling Loudspeakers

The JBL Control 400 Standard Coverage Series brings high-performance audio to accessible price points. Evolving the iconic Control 10 Series, they offer enhanced sound quality, unmatched reliability, installer-friendly features, and a sleek, modern design.

### EN54-24 Life Safety Certified

Control 400 Standard Coverage Series VA models meet EN54-24 life safety certification requirements. That makes them an ideal solution for systems requiring voice alarm speakers to support safe evacuation and guide occupants during emergencies.



▲ Optional White Square and Black Round Grilles Available

White



### Control 412C/T

#### 3" Full-Range Compact Ceiling Loudspeaker

**Frequency Range (-10dB):**  
68 Hz to 17 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
20 W (80 W Peak)

**Impedance / Transformer:**  
8 Ω / 15 W

White



### Control 412C/T-VA

#### 3" Full-Range Compact Ceiling Loudspeaker for Life Safety Applications (EN54-24)

**Frequency Range (-10dB):**  
68 Hz to 17 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
20 W (80 W Peak)

**Impedance / Transformer:**  
8 Ω / 15 W

EN54-24 CERTIFIED

EN54-24 CERTIFIED



White

### Control 414C/T

#### 4" Two-Way Coaxial Ceiling Loudspeaker

**Frequency Range (-10dB):**  
65 Hz to 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
30 W (120 W Peak)

**Impedance / Transformer:**  
8 Ω / 25 W



White

### Control 414C/T-VA

#### 4" Two-Way Coaxial Ceiling Loudspeaker for Life Safety Applications (EN54-24)

**Frequency Range (-10dB):**  
65 Hz to 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
30 W (120 W Peak)

**Impedance / Transformer:**  
8 Ω / 25 W



White

### Control 416C/T

#### 6.5" Two-Way Coaxial Ceiling Loudspeaker

**Frequency Range (-10dB):**  
61 Hz to 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
60 W (240 W Peak)

**Impedance / Transformer:**  
8 Ω / 30 W



White

### Control 416C/T-VA

#### 6.5" Two-Way Coaxial Ceiling Loudspeaker for Life Safety Applications (EN54-24)

**Frequency Range (-10dB):**  
61 Hz to 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
60 W (240 W Peak)

**Impedance / Transformer:**  
8 Ω / 30 W

White



### Control 418C/T

#### 8" Two-Way Coaxial Ceiling Loudspeaker

**Frequency Range (-10dB):**  
57 Hz to 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
90 W (360 W Peak)

**Impedance / Transformer:**  
8 Ω / 60 W

White



### Control 414C/T Micro

#### 4" Two-Way Ceiling Loudspeaker with Low-Profile Enclosure

**Frequency Range (-10dB):**  
69 Hz to 25 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
15 W (60 W Peak)

**Impedance / Transformer:**  
8 Ω / 10 W

White



### Control 414CT Micro Plus


#### 4" Two-Way High-Output Ceiling Loudspeaker with Low-Profile Enclosure

**Frequency Range (-10dB):**  
69 Hz to 25 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
25 W (100 W Peak)

**Impedance / Transformer:**  
- / 25 W

# Control 400 Series



## Enhanced Coverage Ceiling Loudspeakers

The Enhanced Coverage Series includes JBL's Coplanar Radiation Boundary Integrator™ to provide a more even frequency response throughout the coverage area and strikes an elegant performance to cost balance between the Standard and Premium models.

### Integrated Coplanar RBI™ Technology

CRBI™ delivers an especially smooth sound character that remains consistent, clear, and pleasant across a wide coverage area, improving the listening experience for users as they move throughout a space.



▲ Optional White Square and Black Round Grilles Available



○ White

### Control 426C/T-LS

**6.5 inch CRBI-Equipped Two-Way Coaxial Ceiling Loudspeaker for Life Safety Applications**

**Frequency Range (-10dB):**  
72 Hz to 19 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
75 W (300 W Peak)

**Impedance / Transformer:**  
12 Ω / 60 W



○ White

### Control 426LP

**6.5 inch CRBI-Equipped Two-Way Coaxial Ceiling Loudspeaker with Low-Profile Enclosure**

**Frequency Range (-10dB):**  
95 Hz to 19 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
75 W (300 W Peak)

**Impedance / Transformer:**  
12 Ω / 60 W



○ White

### Control 424C/T

**4 inch CRBI-Equipped Two-Way Coaxial Ceiling Loudspeaker**

**Frequency Range (-10dB):**  
75 Hz to 18 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
40 W (160 W Peak)

**Impedance / Transformer:**  
16 Ω / 30 W



○ White

### Control 424LP

**4 inch CRBI-Equipped Two-Way Coaxial Ceiling Loudspeaker with Low-Profile Enclosure**

**Frequency Range (-10dB):**  
75 Hz to 18 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
40 W (160 W Peak)

**Impedance / Transformer:**  
16 Ω / 30 W



○ White

### Control 426C/T

**6.5 inch CRBI-Equipped Two-Way Coaxial Ceiling Loudspeaker**

**Frequency Range (-10dB):**  
72 Hz to 19 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
75 W (300 W Peak)

**Impedance / Transformer:**  
12 Ω / 60 W



○ White

### Control 419CS/T


**8 inch Ceiling Subwoofer**

**Frequency Range (-10dB):**  
47 Hz to 320 Hz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
80 W (320 W Peak)

**Impedance / Transformer:**  
8 Ω / 60 W

# Control 400 Series



## Premium Coverage Ceiling Loudspeakers

The JBL Control 400 Premium Coverage Series delivers seamless flagship coverage for clarity-critical installations. Building on the legendary Control 40 Series, these speakers elevate acoustic performance, ease installation, and embody an ultra-modern design.

## Seamless Radiation Boundary Integrator™ Technology

JBL's proprietary Conical Radiation Boundary Integrator® (RBI™) technology delivers constant directivity coverage, ensuring that listeners enjoy an extraordinarily smooth sound character that remains consistent, clear, and pleasant across the entire coverage area.



▲ Optional White Square and Black Round Grilles Available



○ White

### Control 447C/T

**6.5" RBI™-Equipped Two-Way Coaxial Ceiling Loudspeaker**

**Frequency Range (-10dB):**  
55 Hz to 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
75 W (300 W Peak)

**Impedance / Transformer:**  
8 Ω / 60 W



○ White

### Control 447LP

**6.5" RBI™-Equipped Two-Way Coaxial Ceiling Loudspeaker with Low-Profile Enclosure**

**Frequency Range (-10dB):**  
65 Hz to 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
75 W (300 W Peak)

**Impedance / Transformer:**  
8 Ω / 60 W



○ White

### Control 442C/T

**2.5" Compact Ceiling Loudspeaker**

**Frequency Range (-10dB):**  
130 Hz to 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
15 W (60 W Peak)

**Impedance / Transformer:**  
16 Ω / 12 W



○ White

### Control 445C/T

**5.25" RBI™-Equipped Two-Way Coaxial Ceiling Loudspeaker**

**Frequency Range (-10dB):**  
55 Hz to 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
75 W (300 W Peak)

**Impedance / Transformer:**  
8 Ω / 60 W



○ White

### Control 447HC

**6.5" RBI™-Equipped Two-Way Coaxial Ceiling Loudspeaker for High Ceilings**

**Frequency Range (-10dB):**  
55 Hz to 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
75 W (300 W Peak)

**Impedance / Transformer:**  
8 Ω / 60 W



○ White

### Control 440CS/T



**8" Ceiling Subwoofer with Passive Crossover**

**Frequency Range (-10dB):**  
32 Hz to 300 Hz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
100 W (400 W Peak)

**Impedance / Transformer:**  
8 Ω / 80 W

# Control 200 Series



# Control 300 Series

## Medium-Format Ceiling Loudspeakers

Control 226C/T, 227C and 227CT are premium in-ceiling loudspeakers designed to meet the increasing market demand for premium quality sound in ceiling-mount applications. The Control 200 Series loudspeakers incorporate breakthrough performance features such as best-in-class constant-directivity pattern control to provide a consistent sound throughout the listening area. Especially wide coverage allows fewer loudspeakers to cover the space, reducing both the material and labor cost for the installation. The high-power Kevlar™ reinforced 6.5 inch (165 mm) low-frequency driver along with the titanium-diaphragm compression driver and advanced-technology steep-slope crossover provides superb, wide-bandwidth sound quality.



White

### Control 226C/T

**6.5 inch Coaxial Ceiling Loudspeaker with HF Compression Driver**

**Frequency Range (-10dB):**  
47 Hz to 19 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
100 W

**Impedance / Transformer:**  
8 Ω / 68 W

## Large-Format Ceiling Loudspeakers

Control 300 Series represents the state-of-the-art in large-format ceiling loudspeaker systems. True point-source coax designs, multiple power levels and transformer choices, plus an in-ceiling subwoofer, make it easy to fulfill any system performance requirements. Premium components include Kevlar™-reinforced cones, low-saturation transformers and legendary JBL compression drivers. Constant-directivity coverage, advanced high-slope crossover networks, low system distortion and smooth frequency response provide full, natural music along with exceptional speech intelligibility.



White

### Control 227C


**6.5 inch Coaxial Ceiling Loudspeaker with HF Compression Driver**

**Frequency Range (-10dB):**  
43 Hz to 19 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
100 W

**Impedance / Transformer:**  
8 Ω / NA

For Use with Pre-Install Backcan



White

### Control 227CT

**6.5 inch Coaxial Ceiling Loudspeaker with HF Compression Driver**

**Frequency Range (-10dB):**  
43 Hz to 19 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
100 W

**Impedance / Transformer:**  
8 Ω / 68 W

For Use with Pre-Install Backcan



White

### Control 328C (CT)

**8 inch Coaxial Ceiling Loudspeaker with HF Compression Driver**

**Frequency Range (-10dB):**  
45 Hz to 18 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
150 W

**Impedance / Transformer:**  
8 Ω / 68 W

High Impedance Version Available (Control 328CT)

For Use with Pre-Install Backcan



White

### Control 321C (CT)

**12 inch Coaxial Ceiling Loudspeaker with HF Compression Driver**

**Frequency Range (-10dB):**  
34 Hz to 18 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
200 W

**Impedance / Transformer:**  
5.6 Ω / 68 W

High Impedance Version Available (Control 321CT)

For Use with Pre-Install Backcan



White

### Control 322C (CT)

**High-output 12 inch Coaxial Ceiling Loudspeaker**

**Frequency Range (-10dB):**  
32 Hz to 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
250 W

**Impedance / Transformer:**  
8 Ω / 100 W

High Impedance Version Available (Control 322CT)

For Use with Pre-Install Backcan



White

### Control 312CS

**High-Output 12 inch Ceiling Subwoofer Loudspeaker**



**Frequency Range (-10dB):**  
30 Hz to 4.5 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
250 W

**Impedance / Transformer:**  
8 Ω / NA

For Use with Pre-Install Backcan

# CSS Commercial Series



# 8100 Series

## Ceiling Loudspeakers

CSS Commercial Series provides excellent performance for paging and background music applications including retail stores, restaurants, schools and other public facilities. High sensitivity speakers provide maximum sound level even at low tap settings, and wide dispersion ensures excellent coverage. The drivers all feature a full 25 mm (1 in) diameter voice coil with a Kapton™ coil-former and high-temperature wire for superior power dissipation and long-term reliability.



White

CSS8004

100 mm (4 in) Ceiling Speaker

Frequency Range (-10dB):  
85 Hz to 18 kHz

Transformer:  
5 W

## Ceiling Speakers with a Stylized Grille

High-fidelity performance at a cost-effective price point, the 8100 Series is an easy to install loudspeaker solution for a wide variety of commercial sound applications. The 8100 Series features high sensitivity drivers that deliver maximum sound levels using minimal amplifier power. With its contemporary grille design, 70V/100V taps and open-back design, the 8100 series brings elegance and performance to basic commercial sound systems, or any application not requiring a backcan for installation.



White

8124

4 inch, Full-range In-Ceiling Loudspeaker

Frequency Range (-10dB):  
60 Hz to 18 kHz

Transformer:  
6 W



White

CSS8008

200 mm (8 in) Ceiling Speaker

Frequency Range (-10dB):  
55 Hz to 16 kHz

Transformer:  
5 W



White

CSS8018

200 mm (8 in) Ceiling Speaker

Frequency Range (-10dB):  
50 Hz to 17 kHz

Transformer:  
10 W



White

8128

8 inch, Full-range In-Ceiling Loudspeaker

Frequency Range (-10dB):  
50 Hz to 16 kHz

Transformer:  
6 W



White


8138

8 inch Full-Range In-Ceiling Loudspeaker for use with Pre-Install Backcans

Frequency Range (-10dB):  
95 Hz to 18 kHz


Transformer:  
6 W

# LCT Speakers



## Lay-In Ceiling-Tile Speakers

LCT lay-in ceiling-tile speakers are full-range ceiling speakers designed to lay into suspended grid ceilings, with no cutting of ceiling tiles required, making for an easy and cost-effective installation with a minimum of mess. The low profile depth of only 103 mm (4 in) allows the speaker to fit in locations where deeper loudspeakers do not. These loudspeakers are designed to provide excellent performance for paging and light-to-medium music in a wide variety of applications.



○ White

LCT 81C/T

**Low-Profile Lay-In 24 inch x 24 inch Ceiling Tile Loudspeaker**

**Frequency Range (-10dB):**  
100 Hz to 16 kHz

**Impedance / Transformer:**  
8 Ω / 10W



○ White

LCT 81C/TM

**Low-Profile Lay-In 600 mm x 600 mm Metric Ceiling Tile Loudspeaker**

**Frequency Range (-10dB):**  
100 Hz to 16 kHz


**Impedance / Transformer:**  
8 Ω / 10W





Voodoo Bayou, USA

# Control 60 Series



## Constant-Directivity Pendant Loudspeakers

The Control 60 Series brings renowned JBL sound to rooms and venues with open architecture or high ceilings, while providing superior voice and musical clarity for rooms with difficult acoustics. Easy to install stainless steel hanging hardware is included, featuring redundant suspension cables and UL-listed adjustable height hangers. The Control 60 Series features JBL-exclusive RBI Radiation Boundary Integration™ technology, providing true constant-directivity coverage. Exceptionally wide patterns reduce the number of loudspeakers needed to cover a space.

## Radiation Boundary Integrator™ (RBI)

This unique JBL patented innovation combines a large diameter high-frequency waveguide with low-frequency projection apertures that work in tandem to provide a seamless integration of coverage between the two coaxially mounted drivers. The result is extremely even pattern control and coverage, where all listeners hear a consistent, flat, frequency response. This often allows the use of fewer speakers.



Black / White

### Control 60PS/T

**8 inch Pendant Subwoofer with Crossover**

**Frequency Range (-10dB):**  
42 Hz to 350 Hz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
150 W

**Impedance / Transformer:**  
8 Ω / 110 W



Black / White

### Control 62P

**2.5 inch Ultra-Compact Mid-High Satellite Pendant Loudspeaker**

**Frequency Range (-10dB):**  
150 Hz to 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
15 W

**Impedance / Transformer:**  
16 Ω / NA



Black / White

### Control 64P/T

**4 inch Compact Full-Range Pendant Loudspeaker**

**Frequency Range (-10dB):**  
65 Hz to 15 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
40 W

**Impedance / Transformer:**  
8 Ω / 30 W



Black / White

### Control 65P/T

**Two-Way 5.25 inch Coaxial Pendant Loudspeaker**

**Frequency Range (-10dB):**  
55 Hz to 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
75 W

**Impedance / Transformer:**  
8 Ω / 60 W



Black / White

### Control 67P/T

**Two-Way 6.5 inch Coaxial Full-Range Pendant Loudspeaker**

**Frequency Range (-10dB):**  
58 Hz to 18 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
75 W

**Impedance / Transformer:**  
8 Ω / 60 W



Black / White

### Control 67HC/T

**Two-Way 6.5 inch Coaxial Narrow-Coverage Pendant Loudspeaker**

**Frequency Range (-10dB):**  
75 Hz to 17 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
75 W

**Impedance / Transformer:**  
8 Ω / 60 W



Black / White

### Control 68HP

**High-Power Pendant Loudspeaker**


**Frequency Range (-10dB):**  
52 Hz to 17 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
150 W

**Impedance / Transformer:**  
8 Ω / 68 W



# SLP Series



## Sleek Low-Profile Speakers

SLP sleek, low-profile full-range on-wall loudspeakers provide superior sound and broad, consistent coverage in a sleek, low-profile enclosure that delivers the legendary sound that JBL is known for. These elegantly finished speakers complement any décor and are available in black or white finishes. These stylish, low-profile speakers feature a downward tilt to their aim, allowing them to be installed flat to the wall, making them perfect for venues such as high-end restaurants, hotels, resorts, retail stores, and any installation application calling for a discreet yet elegant look.



Black / White

SLP 12/T

**Sleek, Low-Profile On-Wall Loudspeaker**

**Frequency Range (-10dB):**  
74 Hz to 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
20 W (80 W Peak)

**Impedance / Transformer:**  
8 Ω / 15 W



Black / White

SLP 14/T

**Sleek, Low-Profile On-Wall Loudspeaker**

**Frequency Range (-10dB):**  
70 Hz to 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
30 W (120 W Peak)


**Impedance / Transformer:**  
8 Ω / 25 W



**Wat Pathum Wanaram Temple, Thailand**



# Control Contractor 20 Series



# Control 50 Series

## Surface-Mount Loudspeakers

The Control Contractor 20 Series balances superior fidelity with versatility, ease of installation, and contemporary styling.



Black / White

### Control SB2210

#### Dual 10 inch Compact Subwoofer

**Frequency Range (-10dB):**  
38 Hz to 500 Hz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
400 W

**Impedance / Transformer:**  
8 Ω / NA

## Subwoofer-Satellite Loudspeaker System

The Control 50 Series subwoofer-satellite loudspeaker system provides high-fidelity sound in any location where full-range high-fidelity foreground/ background music is required from a surface-mount system. The Control 50S/T subwoofer can be utilized with either two of four Control 52 satellite loudspeakers. The Control 50 system is mono. Both the Control 50S/T and Control 52 can be intermixed in systems along with the in-ceiling and pendant subwoofer and satellite models to match the form factor requirements of a wide variety of applications and architectures.



Black / White

### Control 52

#### 2.5 inch Surface-Mount Satellite Loudspeaker

**Frequency Range (-10dB):**  
140 Hz to 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
15 W

**Impedance / Transformer:**  
16 Ω / NA



Black / White

### Control 25AV

#### Two-Way 5.25 inch Video Shielded Compact Surface-Mount Loudspeaker

**Frequency Range (-10dB):**  
70 Hz to 23 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
100 W

**Impedance / Transformer:**  
8 Ω / 60 W



Black / White

### Control 25AV-LS

#### Two-Way 5.25 inch Life-Safety Compact Surface-Mount Loudspeaker

**Frequency Range (-10dB):**  
90 Hz to 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
100 W

**Impedance / Transformer:**  
8 Ω / 60 W

EN-54 Compliant and UL Life Safety



Black / White

### Control 29AV-1

#### Two-Way 8 inch Surface-Mount Loudspeaker

**Frequency Range (-10dB):**  
37 Hz to 18 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
150 W

**Impedance / Transformer:**  
8 Ω / 110 W



Black / White

### Control 31

#### Two-Way 10 inch Surface-Mount Loudspeaker

**Frequency Range (-10dB):**  
33 Hz to 19 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
200 W

**Impedance / Transformer:**  
8 Ω / 150 W



Black / White

### Control 50 PACK

#### Surface-Mount Subwoofer-Satellite Loudspeaker System

**Frequency Range (-10dB):**  
32 Hz to 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
100 W

**Impedance / Transformer:**  
4-8 Ω / 80 W



Black / White

### Control 50S/T

#### 8 inch Surface-Mount Subwoofer

**Frequency Range (-10dB):**  
32 Hz to 200 Hz


**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
100 W

**Impedance / Transformer:**  
8 Ω / 80 W



**Shangri-La Jeddah, Saudi Arabia**

# Control CRV Series



## Architectural Loudspeaker

The Control CRV brings high design and versatility to high-finish commercial venues that require a fashionable look. JBL Control CRV loudspeakers are exceedingly versatile, with multiple installation possibilities: wall-mounted aimed straight out, angled down at a 45° aiming axis, mounted spanning the junction of a wall and ceiling, or spanning the junction of two walls. Two, three, or four (with optional PMB pole-mount bracket) Control CRV loudspeakers can be joined together to create loudspeaker solutions for a wide variety of coverage, appearance, and mounting requirements.



Black / White


### Control CRV

**Dual 4 inch Versatile High Design Loudspeaker**

**Frequency Range (-10dB):**  
80 Hz to 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
60 W

**Impedance / Transformer:**  
4 Ω / 30 W



## Wide-Coverage Loudspeaker with HST Technology™

The Control HST utilizes JBL's Hemispherical Soundfield Technology™ to achieve extremely wide coverage of the listening space along with eliminating the primary wall reflection that tends to cause inconsistent sound when loudspeakers are attached to a wall. The wide hemispherical sound field covers from wall to wall, allowing a single loudspeaker to provide full-range sound to a large listening area. This can reduce the number of loudspeakers needed for covering a space, lowering the overall cost for a sound system.



Black / White

### Control HST

**Wide-Coverage Loudspeaker with 5.25 inch LF and Dual Tweeters**

**Frequency Range (-10dB):**  
50 Hz to 20 kHz



**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
75 W

**Impedance / Transformer:**  
8 Ω / 60 W



Coal Drops Yard, UK

# CSS Commercial Series



# Control Pro Series

## Surface-Mount Loudspeakers

As an integral part of the JBL CSS Commercial System Solutions line-up of amplifiers, mixers, and wall controllers, CSS Series Surface-Mount Speakers provide excellent performance for paging and background music applications. CSS-H Paging Horns provide voice range clarity and IP65 capability for applications such as public address and announcement/paging systems. CSS-1S/T is a versatile, compact speaker for background music and speech reproduction.



○ White

### CSS-H15

#### 15 Watt Paging Horn

**Frequency Range (-10dB):**  
400 Hz – 7.5 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
15 W

**Impedance / Transformer:**  
8 Ω / 15 W



○ White

### CSS-H30

#### 30 Watt Paging Horn

**Frequency Range (-10dB):**  
380 Hz – 6 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
30 W

**Impedance / Transformer:**  
8 Ω / 30 W

## Compact Loudspeaker Systems

The classic look of the JBL Control Series installation monitors stems from their initial development as recording studio reference monitors. Offering well-balanced sound, these loudspeakers are ideal for any installation requiring classic professional control monitor performance from a compact source.



● Black

### CSS-1S/T

#### Compact Two-Way 100V/70V/8 Ω Loudspeaker

**Frequency Range (-10dB):**  
85 Hz – 18 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
60 W

**Impedance / Transformer:**  
8 Ω / 10 W



● Black / White

### Control 1 Pro

#### Two-Way 5.25 inch Professional Compact Loudspeaker System

**Frequency Range (-10dB):**  
80 Hz to 20 kHz

**Power Capacity**  
**Cont. Pink Noise (2 hrs):**  
150 W

**Impedance / Transformer:**  
4 Ω / NA



● Black

### Control 2P


#### Two-Way 5.25 inch Compact Powered Reference Monitors

**Frequency Range (-10dB):**  
80 Hz to 20 kHz

**Max SPL:**  
111 dB



# CBT Series



## Passive Controlled-Coverage Column Loudspeakers

CBT Series has ushered in a new era for passive column speaker technology, providing Constant Beamwidth Technology™ with the ultimate in performance, versatility, and affordability. Designed for venues that might typically use larger point-and-shoot speakers, the CBT models incorporate technical advancements that allow them to vastly outperform competitive systems, with a level of user-friendliness that virtually eliminates the challenges of delivering great sound. Many of the models offer adjustable coverage capability to better fit the requirements of a variety of venues, plus user-variable voicing, overload protection, and outdoor capability, with SPL capability as high as 137 dB peak (134 dB continuous program), depending on the model and settings.



Black / White

### CBT 200LA-1

**200 cm (79 in) Tall Constant Beamwidth Technology Asymmetrical Column Speaker**

**Frequency Range (-10dB):**  
80 Hz to 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
400 W

**Impedance / Transformer:**  
8 Ω each / 120 W + 120 W (dual)



Black / White

### CBT 50LA-1

**50 cm (21 in) Tall Constant Beamwidth Technology Column Speaker**

**Frequency Range (-10dB):**  
80 Hz to 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
100 W

**Impedance / Transformer:**  
8 Ω / 60 W



Black / White

### CBT 50LA-LS

**50 cm (21 in) Tall Column Loudspeaker with Eight 50 mm (2 in) Drivers and EN54:24 Certification**

**Frequency Range (-10dB):**  
120 Hz – 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
100 W

**Impedance / Transformer:**  
8 Ω / 60 W



Black / White

### CBT 100LA-1

**100 cm (39 in) Tall Constant Beamwidth Technology Line Array Column Loudspeaker**

**Frequency Range (-10dB):**  
80 Hz to 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
200 W

**Impedance / Transformer:**  
8 Ω / 120 W



Black / White

### CBT 1000

**100 cm (40 in) Tall Very-High Output Asymmetrically Adjustable Extended-Range Line Array Column**

**Frequency Range (-10dB):**  
45 Hz – 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
1000 W

**Impedance / Transformer:**  
4 Ω



Black / White

### CBT 70J-1

**70 cm (27 in) Tall Two-Way Asymmetrical Line Array Column**

**Frequency Range (-10dB):**  
60 Hz – 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
350 W

**Impedance / Transformer:**  
8 Ω / NA



Black / White

### CBT 1000 + 1000E System

**200 cm (80 in) Tall Very-High Output Asymmetrically Adjustable Extended-Range Line Array Column**

**Frequency Range (-10dB):**  
38 Hz – 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
2000 W

**Impedance / Transformer:**  
4 Ω



Black / White

### CBT 70J-1 + 70JE-1 System

**140 cm (54 in) Tall Two-Way Asymmetrical Line Array Column with Extension**

**Frequency Range (-10dB):**  
45 Hz – 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
700 W

**Impedance / Transformer:**  
4 Ω / NA



|            |            |  |  |  |            |
|------------|------------|--|--|--|------------|
| Speech     | ██████████ |  |  |  | Music      |
| Background | ██████████ |  |  |  | Foreground |
| Small      | ██████████ |  |  |  | Large      |
| Low Cost   | ██████████ |  |  |  | High Cost  |

# GSF Series

## Garden Ground-Stake Full-Range Speakers

Weather-resistant JBL GSF garden ground-stake full-range speakers provide superior fidelity and wide coverage in a range of outdoor commercial applications. Available in hunter green and tan finishes, these speakers are the perfect sound solution for diverse outdoor applications including shopping malls, theme parks, sports venues, hospitality venues, and any application calling for a stylish, robust, great-sounding landscape speaker system.



(includes L-bracket and ground stake)



Green / Tan

### GSF3

#### 3 inch Coaxial Full-Range Landscape Loudspeaker

**Frequency Range (-10dB):**  
74 Hz to 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
15 W (60W Peak)

**Impedance / Transformer:**  
8 Ω / 15 W



Green / Tan

### GSF6

#### 6.5 inch Coaxial Full-Range Landscape Loudspeaker

**Frequency Range (-10dB):**  
65 Hz to 20 kHz

**Power Capacity**  
**Cont. Pink Noise (100 hrs):**  
30 W (120 W Peak)


**Impedance / Transformer:**  
8 Ω / 30 W








# Understanding Control Contractor



## Annotations



- \* Speech/Music range based on frequency response.
- \* Any music-capable speaker is also speech capable.
- \* Ratings based on best use of the speaker line's capabilities.
- \* Background/Foreground range based on SPL capability for music content along with typical listening distances.
- \* Small/Large range based on physical size.
- \* Low-Cost/High-Cost range based on product's form-factor market.
- \* For full technical specifications please refer to the product Spec Sheet which can be found on <https://jblpro.com/en>

## Suffix and Prefix Guide

(not all accessories are shown in brochure):

- C**..... Ceiling Speaker
- CT**.....Ceiling Speaker with non-bypassable transformer, for 100V or 70V distributed speaker line
- C/T**..... Ceiling Speaker with bypassable transformer, for either low-impedance or 100V/70V distributed speaker line
- LP**..... Low-Profile Speaker (shallow, for use in ceilings with limited space above ceiling surface)
- HC**..... High-Ceiling Speaker (narrow coverage, which works better for high ceiling applications)
- P**..... Pendant Speaker
- P/T**..... Pendant Speaker with bypassable transformer, for either low-impedance or 100V/70V distributed speaker line
- S**.....Subwoofer (in most cases)
- C-VA**..... Voice Announcement (special certification for use in voice announcement systems)
- LS**..... UL Life-Safety (may also have VA certification)
- AV**..... Audio-Video Shielded (for use close to magnetically sensitive equipment)
- W**.....In-Wall Speaker
- WT**.....In-Wall Speaker with non-bypassable transformer, for 100V or 70V distributed speaker line
- MTC**..... Mounting Bracket or accessory
- WMG and MK**..... WeatherMax™ Grille and Marine-Kit (for extreme weather locations)
- UB**..... U-Bracket
- CM**..... Ceiling-Mount Adapter Arm (for surface-mount speakers)
- NC**..... New-Construction Installation Bracket
- MR**..... Plaster ("Mud Ring") Installation Bracket
- BB**..... Backbox (or backcan)
- SG**..... Square Grille
- RG**..... Round Grille
- TB**..... Tile Bridge
- TR**..... Trim Ring



2026

# CONTROL CONTRACTOR

Scalable, Integrated, Installed Audio Solutions

Where to buy JBL Professional:

