

WIR TX75 PRO

INFRARED TRANSMITTER 2.3,2.8 / 3.3,3.8 MHz



WIR TX75c/d

WIR TX75-S
(sold separately)

[BEAUTY PAIRED WITH UNPARALLELED COVERAGE]

NEW The WIR TX75 PRO infrared transmitters have phoenix connectors for the line inputs - the TX75c operating at 2.3/2.8 MHz, and TX75d operating at 3.3/3.8 Mhz. These PRO transmitters ensure participants in your conference room, courtroom, classroom or other mid-sized venue receive direct, clear communication of your message without sacrificing security. The sleek and stylish TX75 PRO is designed to maximize coverage area up to 12,000 square feet* in single-channel mode, when used with a WIR RX22-4 receiver. Two slaves (WIR TX75-S)

can be added for additional coverage up to 12,000 square feet each* (36,000 square feet total), when mounted up to 100 feet from the master transmitter. Placing additional slaves in the same room increases coverage and enhances freedom of movement. A single CAT-5 cable carries both power and signal to slaves—truly a one-cable connection. Mounting bracket and international power supply are included. 5-year warranty.

*Operating range varies based on receiver used. See emitter specifications for coverage area by receiver type.

WIR TX75 PRO

INFRARED TRANSMITTER 2.3,2.8 / 3.3,3.8 MHz



FEATURES/BENEFITS

- New! Improved Range - up to 12,000 square feet* in single-channel mode, when used with a WIR RX22-4 receiver.
- Looks great! Sleek, professional styling complements room aesthetics.
- Front cover can be painted to match décor.
- TX75-S slave emitter available for use with TX75 (sold separately)
- Headset, stethoset and body-pack receivers available for use with TX75 (sold separately).
- Robust digital communication bus between master and slave units reduces interference.
- Master unit has troubleshooting lights built in to simplify installation.
- Separate Phoenix audio inputs for each channel (2.3/2.8 MHz on the TX-75c, and 3.3/3.8MHz on the TX-75d) accept balanced or unbalanced line level inputs; use together for stereo operation or separately for mono.
- Unit senses if only one channel is in use and doubles the output power on that channel for twice the coverage.
- Green power – if no audio is present after a few minutes, unit automatically disables power to IR diodes, reducing power consumption by 80 percent.
- 5-year warranty

SYSTEM INCLUDES

- (1) WIR TX75c (or WIR TX75d) PRO infrared transmitter
- (1) BKT 024 wall / ceiling mounting bracket
- (1) TFP 046 international power supply with WLC 004 U.S. mains AC plug

APPLICATIONS

- Courtrooms
- Conferences
- Houses of Worship
- Universities
- Cinema

*Operating range varies based on receiver used. See emitter specifications for coverage area by receiver type.