EN54-24

ROUND METAL CEILING CSA mini

TECHNICAL SPECIFICATIONS

EN54-24:2008

Certificate No: 0359-CPD-0120 TYPE A

ELECTRICAL

Rated power, Watts	6
Tappings 100 volt line, Watts	6/3/1.5/0.75/0.25
Transformer Impedance, Ohms 100V	1.67k/3.33k/6.66k/13.3k/39.9k
Tappings 70.7 volt line, Watts	3/1.5/0.75/0.375/0.125
Driver impedance, Ohms	8
Effective Frequency Range, Hz (BSEN60268-5)	180 - 18K
S.P.L. @ 4m, 1watt, dB,1/3 Octave, 1kHz	65
S.P.L. @ 1m, 1watt, dB, Test Signal Bandwidth 100Hz-10kHz	95
S.P.L. @ 4m, Full power, dB, 1/3 Octave 1kHz	72
S.P.L. @ 1m, Full power, Test Signal Bandwidth 100Hz-10kHz	102
Dispersion at 1k/2k Hz, Degrees	180/180

ENVIRONMENTAL

IP Rating	21
Max/Min Ambient Temp	55°/-10°c
Relative Humidity	≤95%

MECHANICAL

Height 120, Ø239
1.5
White RAL9016
Steel
Torsion springs
Ø200

RCS6FT/ENC is supplied with capacitor for DC line monitoring

RCS6FT/EN & C are BS5839 Part 8 Compliant

Recommended for internal use only unless fitted with CRSC/6 weatherproof cover

Manufacturer reserves the right to alter specifications without notice November 2018

RCS6FT/EN RCS6FT/ENC ROUND METAL CEILING LOUDSPEAKERS

Gland not included Unit:mm Unit:mm (Grife) 10mm 4 239mm



RCS6FT/EN & RCS6FT/ENC * unit fitted with Capacitor

EN54-24



WITH TRANSFORMER: 100V/70V LINE

\sim	WHITE WIRE PLUS TAPPING					BLACK
100V	0.25W	0.75W	1.5W	ЗW	6W	СОМ
70V	0.125W	0.375W	0.75W	1.5W	ЗW	сом
$IMP(\Omega)$	39.9K	13.3K	6.66K	3.33К	1.67K	

DISPERSION ANGLES

		HORIZONTAL	VERTICAL
1 OCT.PINK NOISE	500 Hz	180°	180°
1 OCT.PINK NOISE	1 K Hz	180°	180°
1 OCT.PINK NOISE	2K Hz	180°	180°
1 OCT.PINK NOISE	4K Hz	70°	70°

FREQUENCY RESPONSE



The RCS6FT/EN & ENC have been tested for 100 hours at a maximum power of 6W. Both units did not deviate by more than +/- 3dB.The frequency response and impedance curves remained constant throughout the test period. All results are in full compliance with the requirements of EN54-24.



Penton UK Ltd

Unit 2 Teville Industrials | Dominion Way | Worthing | West Sussex | BNI4 8NW T: +44 (0)1903 215315 | F: +44(0)1903 215415 | E: SALES@PENTONUK.CO.UK

www.pentonuk.co.uk

