




DNH

ISO 9001 CERTIFIED

SAFE-15(T)

Commercial Audio Solutions Ltd
The Old Barn, Whitecroft Farm
Strines, Derbyshire. SK22 3AH.
Tel: 01663 767888

www.commercialaudiosolutions.com



Sound pressure levels at 1W/1m

SPL vs Freq



Specifications

Material / Color	Aluminum / White /Red
Mounting	4 screws
Termination	Ceramic terminal
Weight w/transformer	1,7 kg
IP-rating	67
Max. / min. amb. temp	150°C / -50°C
Rated / max. power	15 W / 30 W
SPL 1W/1m	101 dB
SPL rated power	113 dB
Effective freq. range	500 – 6000 Hz
Dispersion (-6dB) 1kHz / 4kHz	175° / 110°
Directivity factor, Q	NA
Options	Impedances, colors, labels

Installation, Operation and Maintenance Procedures

- Open the cabinet using the enclosed Allen key to loosen the screws on three sides of the cabinet.
- Lead cable through the cable gland and connect to terminal 70V (white – green) or 100V (white – red).
- Choose required power on the transformer.
- Fasten the mounting plate to wall or ceiling by four screws.
- Close the cabinet by fasten three screws on three sides of the cabinet.
- For optimum performance, always use the correct voltage / power and operate within the frequency limits as stated.
- Do not open loudspeaker when energized.
- This loudspeaker is supplied with a two years warranty against defective workmanship.

DNH reserves the right to alter specifications without notice

